

Kingston Flip-Arched Table Specifications:

Kingston Flip-Arched incorporates a tilting top resulting in vertically stacking table. Its structure allows nesting in the flipped position. Single point release mechanism is easy to use when flipping any size top. Locking dual wheel casters are standard. Heavy duty all-welded lock ensures safety. Heavy duty beam prevents top from sagging. Special•T table tops are nominal 1-1/4" thick. Core is 1-1/8" thick 45# M3 industrial strength density particle board. The top surface is laminated with High Pressure Laminate (HPL) and the bottom is covered with a balance backer. Standard edge is 3mm PVC. Other edges available.*

- Premium Vinyl
- Premium Vinyl with Flat Sides
- Wood
- PurTech Urethane
- PurTech Urethane with Flat Sides
- PurWood Urethane
- PurWood Urethane with Flat Sides

*Custom edges may not be available with all shapes and sizes.
See web link: http://www.specialt.net/tables/flip_1/slim-flip_arched/

Construction:

- Bolted/welded
- Table height: 29"
- Columns: 2" diameter, 14 gauge steel
- Feet: 2" diameter, 14 gauge steel,
- Casters: skate wheel locking casters
- When stacked, each table adds 4-3/4" to the depth and 2-1/4" to the length of the table.
- Finish: powder coat
- Mounting beam: heavy duty tubular steel with single point positive locking release mechanism (3) 5" x 8" x 7/32" steel hinges
- 500 lbs. vertical load rating per table

Options:

- Leveling glides
- Integra folding modesty panel
- Grommets
- Wire management
- Table joiners

Additional Information:

- For easy installation, tops are pre-drilled. Legs position is 5" from the edge to the center of the column.
- Table is available in 24" and 30" width and 48", 60" and 72" length. 54" and 66" long tables are also available with the base 11" shorter than top.
- Standard lead time is 15 business days. Large orders may require additional time.
- Custom size tables are subject to 9-12 week lead time.

*** When Kingston Flip tables are placed together, we recommend using Quick Align table connectors to ensure that tables are leveled properly.**



One point positive locking release mechanism



Intertek

Compliant with
BIFMA X7.1 Standard